

OUR MOST **POWERFUL** DRILL









E-CLUTCH[™] SYSTEM AND MECHANICAL CLUTCH Improves user control

> • 60V MAX* BRUSHLESS MOTOR Maximizes power, runtime and durability No need to change brushes



QUICK-SHIFT Easily change speed without having to feather the trigger



2-POSITION SIDE HANDLE

LED LIGHT

CHUCK KEY HOLDER



THE ADVANTAGE

*Maximum initial battery voltage (measured without a workload) is 60 volts. Nominal voltage is 54. **Using DCB609 DEWALT FLEXVOLT® Battery tBattery to the separately

DRILL UP TO 75 HOLES IN 2" SPF#2 WOOD** USING DW1642 4-5/8" SELF-FEED BIT[†]

60V MAX* IN-LINE STUD & JOIST DRILL

DCD470

UP TO **48% MORE POWER** THAN CORDED MILWAUKEE® SUPER HAWG^{*}

[‡]TESTED MILWAUKEE[®] 1680

SPECIFICATIONS TOOL WARRANTY Chuck Size 1/2" **No Load Speed** 0-400/0-1320 RPM **Quick-Shift** Yes **LIMITED** FREE MONEY BACK WARRANTY SERVICE **GUARANTEE Unit Watts Out** Up to 2600 W **BATTERY WARRANTY** (3.5 MAX HP) Weight (Tool Only) 14.4 lbs **Available Options DCD470B, DCD470X1** LIMITED FREE WARRANTY SERVICE





RELATED PRODUCTS



DCD470X1 60V MAX* IN-LINE STUD & JOIST DRILL KIT



DCD460B 60V MAX* VSR STUD & JOIST DRILL (Tool only)



DCD460T1 60V MAX* VSR STUD & JOIST DRILL KIT



DCD460T2 60V MAX* VSR STUD & JOIST DRILL KIT





Copyright ©2018 DEWALT. The following are examples of trademarks for one or more DEWALT power tools and accessories: the yellow and black color scheme; the "D"-shaped air intake grill; the array of pyramids on the handgrip; the kit box configuration; and the array of lozenge-shaped humps on the surface of the tool. Milwaukee® is a registered trademark of Milwaukee Electric Tool Corp.

DCD470SS