





THE ADVANTAGE

\*Maximum initial battery voltage (measured without a workload) is 20 volts. Nominal voltage is 18.

INCLUDES

DCD996, DCF887, (2) DCB205, DCB115, (2) Pre-installed LANYARD READY™ Attachment Kit, Contractor Bag



**DEWALT® LANYARD READY™** integrated solutions offer options to tether select corded and cordless tools to rigid structures on jobsites when working at height with a maximum lanyard length of 2m, helping to secure the tool in case it is dropped.



20V MAX\* XR® 2-TOOL COMBO KIT WITH LANYARD READY™ ATTACHMENT POINTS

DCK299P2LR



**LANYARD READY™ Attachment Point Kits are also available for** installation on select DEWALT® tools at your local service center:

## **Tool Connection Point Kit - N547085**

Includes: (1) Tool Connection Point, (2) Battery Lanyard Connection Points with Carabineer, Required Installation Hardware

## **Battery Lanyard Connection Point Kit - N601289**

Includes: (1) Battery Lanyard Connection Point with Carabineer, Required Installation Hardware

Contact your service center for more information. www.dewalt.com/support/find-a-service-center

## MORE LANYARD READY™ COMPATIBLE TOOLS COMING SOON









**BATTERY WARRANTY** 

1-800-4-**DEWALT** 

www. **DEWALT**.com

Copyright ©2018 DEWALT. The following are trademarks for one or more DEWALT power tools, accessories, anchors and concrete adhesives: The yellow and black color scheme; the "D"-shaped air intake grill; the array of pyramids on the handgrip; the kit box configuration; and the array of lozenge-shaped humps on the surface of the tool.